
KEMET Part Number: PME261KE7100KR30

(P561EL105K220A)



Film, Metallized Paper, Commercial Grade, PME261/P561, 1 uF, 10%, 400 V, 85C, Lead Spacing = 25.4mm



Dimensions	
L	30.5mm MAX
Н	22mm MAX
Т	15.3mm MAX
S	25.4mm +/-0.4mm
LL	30mm +5mm
F	1mm +/-0.05mm

Packaging Specifications	
Packaging:	Bulk
Packaging Quantity:	75

General Information		
Dielectric:	Metallized Paper	
Style:	Radial	
Series:	PME261/P561	
Features:	Pulse	
RoHS:	Yes	
Lead:	Wire Leads	
Construction:	Molded	
Miscellaneous:	AC Operation: 70C MAX	

Specifications		
Capacitance:	1 uF	
Capacitance Tolerance:	10%	
Voltage DC:	400 VDC	
Voltage AC:	220 VAC	
Temperature Range:	-40/+100C	
Rated Temperature:	85C	
Dissipation Factor:	1.3% 1kHz	
Insulation Resistance:	12 GOhms	
Max dVdt:	220 V	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

