



LEAD FINISH: SILVER	
BUSHING FINISH: SILVER	
CAPACITANCE	10000pF GMV \diamond 24
TEMP. RANGE	-55°C TO 125°C
CURRENT	10 AMP MAX.
WORKING VOLTAGE	125°C 300 VDC MAX.
D.C. RESISTANCE	.01ohms MAX.
MIN. I.L. PER MIL-STD-220 AT 25°C NO LOAD	
FREQ. MHz	I.L. (db)
1	--
10	20
100	38
1 GHz	50
SCHEMATIC 	
MARKING: PART: S103V \diamond 24 BAG: 54-790-021 DATE CODE QTY/BAG (200 MAX.)	

- NOTES:
 1. MAXIMUM MOUNTING TORQUE = 1.5lb-in.
 2. HARDWARE IS INCLUDED.

	24	23	22	REV. NO.	TOLERANCES UNLESS OTHERWISE SPECIFIED	 SPECTRUM CONTROL INC.	ERIE, FAIRVIEW PENNSYLVANIA
	CN 204563	CN 194476	CN 184931	CHANGE NOTICE	Fractions ± 1/64		Dwn. KAUFFMAN
					Dec. .xx±	Ckd. 11/15/01	
					Dec. .xxx±.010	Apvd.	
					Angles ±0° 30'	Scale NONE	54-790-021
					CODE IDENT. NO. QLSP2		