



03

LEAD FINISH: SOLDER	
EYELET FINISH: SILVER	
CAPACITANCE	22nF GMV
TEMP. RANGE	-55°C TO 125°C
CURRENT	10 AMP MAX.
WORKING VOLTAGE	125°C 70 VDC MAX.
D.C. RESISTANCE	.01ohms MAX.
MIN. I.L. PER MIL-STD-220 AT 25°C NO LOAD	
FREQ. MHz	I.L. (db)
10	35
100	70
1 GHz	70
10 GHz	70
SCHEMATIC 	
MARKING: PART: NONE BAG: SCI 1233F-000 DATE CODE LOT# QTY/BAG (200 MAX.)	



NOTES:
1. MAXIMUM INSTALLATION TEMP.: 500°F

			03		REV. NO.	TOLERANCES UNLESS OTHERWISE SPECIFIED	api  technologies corp.	FAIRVIEW PENNSYLVANIA		
			02		CHANGE NOTICE	Fractions ± 1/64			Dwn. KAUFFMAN	Description
			01			Dec. .xx±	Date 02-24-15	Pi SOLDER-IN FILTER		
			00			Dec. .xxx± .010	Engr. McALEVY			
						Angles ±0° 30'	Scale NONE			
						CODE IDENT. NO. OLSP2				